



CLUB CAR CARRYALL 1500

4x4 Utility Vehicle

Diesel

544kg payload

BRADSHAW
ELECTRIC • VEHICLES

STANDARD EQUIPMENT & OPTIONS

	MODEL	1500D
VEHICLE OVERVIEW	Configuration	4 wheel
	Rack and pinion with tilt steering	•
	Independent double A-arms with coil-over shocks (front)	•
	Semi-independent four link solid axle (rear)	•
	Tubular aluminium chassis	•
ENGINE	Engine	Diesel Kubota D722 Industrial grade Liquid cooled
	Cubic capacity (cc)	719
	Cylinders	3 Cylinder OHV
	Horsepower	20.0 hp (15.0 kW) rated @3600 RPM
	Maximum torque	45.0 Nm
	Fuel system	Mechanical Injection
	Fuel capacity	25 Litres
TRANSMISSION	Speed	40 kph
	Wide ratio Continuously Variable Transmission (CVT)	•
	Gear Selection: Forward/Neutral/Reverse	•
	Gear ratio	3.7 :1 (low) 0.59:1 (high)
BRAKING SYSTEMS	Single pistol hydraulic disc brakes (rear)	•
	Twin pistol hydraulic disc brakes (front)	•
	Mechanical park brake	•
LIGHTS	Twin headlights Twin tail and brake lights	•
	Upgrade lighting includes Twin headlights, Twin side lights, Twin tail and brake lights, Indicators, Hazard warning lights, Reverse light, 7 pin trailer socket	○
	Amber flashing beacon mounted on pole or cab	•
	Blue spot warning light - front only	○
	Blue spot warning light - front & rear	○
	Rear mounted 12 volt working light	○
INSTRUMENTS	Horn	•
	Automatic audible warning in reverse	•
	Keypad in place of standard key switch	○
TYRES	All-terrain 25 x 10.5-12, 4-ply	•
	Mud tyres	○
	Tyre sealant puncture prevention for pneumatic tyres	○
TOW HITCH	No tow hitch fitted	•
	Combined 50mm ball and 25mm single jaw	○
	Tow hitch specific for site requirement	○
CAB	4 point ROPS over head frame	•
	Canopy top and acrylic front screen with 4 point ROPS over head frame	○
	PVC weather protection for use with canopy top with 4 point ROPS over head frame	○
	Safety front screen and wiper for use with canopy top in place of acrylic front screen with 4 point ROPS over head frame	○
	Enclosed Cab - Slam Doors <ul style="list-style-type: none"> • Lockable slam glass doors, • Sliding drivers door window • Safety front and rear screens • Front wiper • Interior mirror • Exterior mirrors 	○
	Cab heater	○
	Rear mounted camera with display screen	○

MODEL		1500D
SEATING	Driver and single passenger bench seat with black seat cushions	●
	Two inertia lap seat belts	○
	Two high visibility inertia lap seat belts (interlock fitted to drivers seat only)	○
MIRRORS	Exterior mirrors (canopy top only)	○
	Interior fish eye mirror (cab option only)	○
LOAD BED	Aluminium cargo box complete with dropdown tailgate and anti-slip floor lining	●
	Cargo box dimensions (LxWxH mm)	1240 x 1265 x 280
	Aluminium cargo box with additional cage body	○
	Aluminium cargo box with PVC cover	○
	Box Van	○
	Electric tipper	●
MISC	Lockable aluminium tool box	○
	1kg dry powder fire extinguisher	○
COLOUR	Chassis: Tubular aluminium	●
	GE Geloy high-impact, scratch-resistant, injection moulded colour, Automotive finish	●
	Custom colour. Chassis Aluminium. Nose cone to customer's single colour specification. RAL number to be supplied at time of order	○
DIMENSIONS & CAPACITY	Overall length (mm)	3165
	Overall width (excluding mirrors) (mm)	1485
	Kerb weight (kg)	703
	Total vehicle capacity (kg)	544
	Payload capacity (kg)	363
	Towing capacity (kg)	907
	Turning radius (mm)	3623





BRADSHAW ELECTRIC VEHICLES

New Lane

Stibbington

Peterborough

PE8 6LW

enquiries@bradshawev.com

www.bradshawEV.com

01780 782 621

All data and specifications are in accordance with information available at the time of publication and are subject to change without notice.

Some of the vehicles shown are may be fitted with optional equipment or accessories that are available at extra cost.

This brochure supersedes all previous publications.
Issue: July 2020

BRADSHAW
ELECTRIC • VEHICLES