

Club Car

CARRYALL 700

UNMATCHED
VERSATILITY



EXCEPTIONAL
RELIABILITY

- 1500 lb. (680.3 kg) total vehicle capacity
- Rustproof, aircraft-grade aluminum frame is stronger than competitors' steel frames and resists corrosion.
- 14-hp rated overhead cam engine with EFI (Electronic Fuel Injection) and side-entry fuel tank improves fuel efficiency by as much as 50%.
- Cockpit style interiors, ergonomic dash and improved hip restraints provide one-of-a-kind comfort.
- Integrated track attachment system, optional tool holders, bed dividers and cargo tie downs increase versatility and save bed space.
- The industry's only standard on-board high-efficiency charger with cord retractor
- The industry's longest and strongest warranty



1,000 JOBS. ONLY ONE
CARRYALL

CARRYALL 700

	ELECTRIC	GASOLINE
Motor/Engine**	48-volt DC	Subaru, 4-cycle, OHC
Controller	500 Amp - Solid State	-
Displacement	-	404 cc
Cylinders	-	Single
Valving	-	Overhead Cam
Cooling	-	Air Cooled
Horsepower (Rated)	3.7 hp (2.7kW) rated; Peak 20 hp (14.9 kW)	14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940
Max Torque	71 ft-lb (96.2 N-m) rated @ 1450 RPM	19.91 ft lb (27.0 N-m) rated @ 2400 RPM
Lubrication	-	Splash lubrication
Governor	-	Ground Speed
Transmission	Direct drive, double reduction helical gear	Continuously Variable Transmission (CVT)
Gear Selection	Forward/Neutral/Reverse	
Gear Ratio	12.32:1	11.47:1 forward;15.63:1 reverse
Ignition	-	Capacitive Discharge
Battery	Eight 6-volt Flooded Lead Acid	12-volt 500 CCA 105 min Reserve
Charger	DeltaQ QuiQ (1 kW High Frequency)	-
Headlights	Two 37.5 Watt Halogen	
Fuel Delivery System	-	Electronic Fuel Injection (EFI)
Capacity	-	5.5 gal (20.8 L)
Steering Mechanism	Self-adjusting Rack and Pinion	
Suspension (Front)	Independent leaf spring with dual hydraulic shocks	
Suspension (Rear)	Semi-independent leaf spring with dual hydraulic shocks	
Brakes	4-wheel Mechanical Drum	
Park Brake	Foot Operated, Multi-lock	
Body (Front & Finish)	ArmorFlex with automotive paint/clearcoat	
Body (Frame & Rear)	Aluminum	
Tires (Front)	20 x 10-10, 6-ply, Premium Tread	
Tires (Rear)	20 x 10-10, 6-ply, Premium Tread	
Wheelbase	99.1 in (251.7 cm)	
Overall Height	47.1 in (119.6 cm)	
Overall Length	137.5 in (349.3 cm)	
Bed L x W x H (Cargo Box)	65.5 x 47.5 x 10.5 in (166.3 x 120.6 x 26.6cm)	
Ground Clearance (Differential)	5.6 in (14.2 cm)	5.2 in (13.2 cm)
Track Width (Front)	36.6 in (92.9 cm)	
Track Width (Rear)	39.5 in (100.3 cm)	
Max Width (w/o Mirrors)	50.3 in (127.7cm)	
Outside Clearance Circle (Dia.)	340.5 in (864.9 cm)	
Curb Weight (with Batteries)	1475 lb (669 kg)	993 lb (450.4 kg)
Total Vehicle Capacity	1500 lb (680.3 kg)	
Bed Load Capacity	1000 lb (453.5 kg)	
Towing Capacity	1500 lb (680.3 kg)	
Combined Gross Vehicle Capacity	1500 lb (680.3 kg)	
Speed	5-17 mph (8-27 km/h)	15-17 mph (24-27 km/h)
Warranty	4 yr limited battery warranty 3 yr limited powertrain/frame 2 yr limited remaining vehicle	3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle



Wheel Covers



Canopy Top




Brush Guard



Flatbed



Cargo Box



Stakeside Kit



Rear Receiver Hitch



Enclosed Cab



Range Cab



Body Colors

** Engine horsepower and torque specifications are provided by the engine manufacturer. Actual horsepower and torque in use may differ and are dependent on environmental conditions as well as maintenance condition of the engine.
(S) Standard Color; (P) Premium Color

