



CLUB CAR TEMPO 2+2

4 Seat Personnel Carrier

STANDARD EQUIPMENT & OPTIONS

	MODEL	LEAD ACID	LITHIUM	PETROL
VEHICLE OVERVIEW	Configuration	4 seats	4 seats	4 seats
	Self-adjusting rack and pinion steering	•	•	•
	Independent leaf spring with dual hydraulic shocks (front)	•	•	•
	Independent leaf spring with dual hydraulic shocks (rear)	•	•	•
	Aluminium chassis	•	•	•
ELECTRIC	Battery	(6) 8-volt, single point watering system	3.1 kW Stored Energy 60 Amp Capacity	-
	Charger	48 VDC 13.5 amp DC high frequency solid state charger	650 Watt Charger (standard) 900 Watt Charger (optional)	-
	Controller	250 Amp	235 Amp (standard) 375 Amp (optional)	-
	Horsepower (rated)	3.3 hp	4.7 hp	-
PETROL ENGINE	Engine	-	-	Kohler, Overhead Valve
	Cylinders	-	-	404 cc
	Horsepower	-	-	14.0 hp (10.3 kW) rated @3600 RPM
	Maximum torque	-	-	27.0 Nm rated @2400 RPM
	Fuel system	-	-	Electronic Fuel Injection (EFI)
	Fuel capacity	-	-	23 Litres
TRANSMISSION	Direct drive, double reduction helical gear	•	•	-
	Gear Selection: Forward/Neutral/Reverse	•	•	•
	Continuously Variable Transmission (CVT)	-	-	•
	Gear ratio	12.32 : 1	12.32 : 1	11.8:1 (forward) 17.1:1 (reverse)
BRAKING SYSTEMS	Rear mechanical drum brakes	•	•	•
	Electronic regenerative braking under deceleration	•	•	-
	Foot operated park brake	•	•	•
	Hand operated park brake (replaces foot park brake)	○	○	○
LIGHTS	Single headlights	•	•	•
	Upgrade lighting includes: Twin headlights, Twin side lights, Twin tail and brake lights, Indicators, Hazard warning lights, Reverse light	○	○	○
	Amber flashing beacon mounted on pole or cab	•	•	•
	Blue spot warning light - front only	○	○	○
	Blue spot warning light - front & rear	○	○	○
	Rear mounted 12 volt working light	○	○	○
CONTROLS / AUDIBLE WARNINGS	Speed	8-24 kph	8-24 kph	19-24 kph
	Emergency stop button	•	•	-
	Horn	•	•	•
	Automatic audible warning in reverse	•	•	•
	Automatic white noise audible warning in forward	○	○	-
INSTRUMENTS	Battery discharge indicator	•	•	-
	Hour meter	•	•	-
	Keypad in place of standard key switch	○	○	○
	12 volt charging socket	○	○	○
TYRES	Pneumatic tyres	•	•	•
	Foam filled puncture proof	○	○	○
	Foam filled puncture proof non marking	○	○	○
	Extra-Traction Rear Tires	○	○	○
	Tyre sealant puncture prevention for pneumatic tyres	○	○	○

	MODEL	LEAD ACID	LITHIUM	PETROL
CAB	Un-cabbed	○	○	○
	Canopy top and acrylic front screen	○	○	○
	PVC 3-sided weather protection for use with canopy top	○	○	○
	Safety front screen and wiper for use with canopy top in place of acrylic front screen	○	○	○
	Rear mounted camera with display screen	○	○	○
SEATING	Seats	4	4	4
	Fixed seats	●	●	●
	Fold-down rear facing seat (not available with PVC 3-sided weather protection)	○	○	○
	Driver and single forward facing passenger	●	●	●
	Two rear facing passengers	●	●	●
MIRRORS	Black seat cushions	○	○	○
	Four inertia lap seat belts	○	○	○
	Interior and exterior mirrors (canopy top only)	○	○	○
MISC	Interior fish eye mirror (canopy option only)	○	○	○
	1kg dry powder fire extinguisher	○	○	○
COLOUR	Chassis: aluminium	●	●	●
	Panels: White armourflex with automotive paint / clear coat	●	●	●
	Custom colour. Chassis aluminium. Panels to customer's single colour specification. RAL number to be supplied at time of order	○	○	○
DIMENSIONS & CAPACITY	Overall length (mm)	2642	2642	2642
	Overall width (excluding mirrors) (mm)	1201	1201	1201
	Kerb weight (kg)	465	465	465
	Total vehicle capacity (kg)	363	363	363





BRADSHAW ELECTRIC VEHICLES

New Lane

Stibbington

Peterborough

PE8 6LW

enquiries@bradshawev.com

www.bradshawEV.com

01780 782 621

All data and specifications are in accordance with information available at the time of publication and are subject to change without notice.

Some of the vehicles shown are may be fitted with optional equipment or accessories that are available at extra cost.

This brochure supersedes all previous publications.
Issue: September 2021

BRADSHAW
ELECTRIC • VEHICLES